

Hydraulische Handzange HP 130 C


mit C-Presskopf, 180° drehbar

- ▶ Doppelkolben-Pumpe für schnelles Anfahren des Presseinsatzes
- ▶ Automatisches Überdruck-Sicherheitsventil
- ▶ Öffnungsweite: 27 mm
- ▶ Presskraft: 130 kN

Hydraulic hand-operated tool HP 130 C

with C-compression head, rotating 180°

- ▶ Double piston pump for rapid motion of the die-set
- ▶ Automatic safety relief valve to avoid overpressure
- ▶ max. open size: 27 mm
- ▶ Force of pressure: 130 kN



Material material	Pressform compression form	Pressbereich compression range mm ²	Länge length mm	Gewicht weight kg	Kat.-Nr. cat.-no.
Cu	Sechskantpressung, handelsüblich Hexagonal pressing, standard-type	6 - 300	520	6,1	58004 - 00
Cu + Al	Sechskantpressung, DIN Type Hexagonal pressing, DIN type	6 - 300			
Cu	Dornkerbung Deep indent pressing	6 - 240			
Cu	Adenendhülsen Pressung trapezoidal pressing	10 - 185			
Cu + Al	Oval-Pressung oval pressing	10 - 95			
Cu + Al	Vorrunden Prerounding	25 - 240			
Cu	REMA WMS - Pressung REMA WMS - pressing	10 - 95			
Transportkoffer/Transport case			650	4,3	58005 - 04
Presseinsätze ab Seite 141 /Dies on page 141					

