





- All punchers have a lateral ejection for the waste piece. No getting stuck inside the die.
- For mild steel (F = 370 N/mm²).
- Punchers are delivered in stable plastic boxes.
- When placing an order for hydraulic operation please specify the hydraulic model.



Size mm				Spare parts				
	Max. material thickness mm / Mild Steel (F = 370 N/mm²)	For operation by	ProdNo. Puncher complete	ProdNo. Tie bolt	ProdNo. Locking nut or bridge	ProdNo. BB pressure nut	ProdNo. Adapter for hydraulics	Pre-drilling Ø mm
17,0 X 19,0	2,0		01317	01347	01351	01352	01353	14
21,8 x 25,8	2,0		01318	01360	01351	01359	01361	17
22,0 X 30,0	2,0		01319	01360	01351	01359	01361	17
22,0 X 42,0	2,0		01320	01360	01351	01359	01361	17
25,0 X 50,0	2,0		01332	01360	01418	01359	01361	17
45,0 X 92,0	2,0		01314	01344	01349			24
46,0 x 92,0	2,0		01329	01344	01349			24
68,0 x 138,0	3,0		01330	01343	01358			30

Punching Tool Sets - Rectangular for heavy connectors Made in Germany by ALFRA

For mild steel ($F = 370 \text{ N/mm}^2$).



4 centering mandrels are placed in the correct position at the die. When die and punch are pressed against each other, the drilling position gets marked on the interjacent work sheet.

These 4 marks can be used as a drilling template.

With help of the twist drill, the drilling assembly for connectors can be done easily.



			Spare pares					
Size mm	Max. material thickness mm/Mild Steel (F = 370 N/mm²)	For operation by	Number of pins	ProdNo. Puncher complete	ProdNo. Tie bolt	ProdNo. Locking nut	Pre-drilling Ø mm	
36,0 x 52,0	2,0		6-pin	01325	01344	01350	24	
36,0 x 65,0	2,0		10-pin	01326	01344	01350	24	
36,0 x 86,0	2,0		16-pin	01327	01344	01350	24	
36,0 x 91,0	2,0			01323	01344	01349	24	
36,0 x 112,0	2,0		24-pin	01328	01344	01357	24	
46,0 x 86,0	2,0			01322	01344	01349	24	
46,0 X 112,0	2,0			01324	01343	01349	30	

Other sizes available upon request.