



Presskopf C 130

mit Hydraulik-Zylinder zum Anschluss an Hydraulik-Pumpen

- ▶ Inkl. Kupplungsniessel
- ▶ Sechskant-Pressseinsätze nach DIN 48083/Blatt 4
- ▶ Für Gesamtkabeldurchmesser bis 25 mm
- ▶ Betriebsdruck: max. 700 bar
- ▶ Presskraft: 130 kN

Compression head C 130

With hydraulic-cylinder for connecting to hydraulic-pumps

- ▶ Incl. coupling male
- ▶ Hexagonal-die-sets according to DIN 48083/page 4
- ▶ For total cable-diameter up to 25 mm
- ▶ Working pressure: max. 700 bar
- ▶ Force of pressure: 130 kN



Material material	Pressform compression form	Pressbereich compression range mm ²	Länge length mm	Gewicht weight kg	Kat.-Nr. cat.-no.
Cu	Sechskantpressung, handelsüblich Hexagonal pressing, standard-type	6 - 300	250	3,9	58001 - 01
Cu + Al	Sechskantpressung, DIN Type Hexagonal pressing, DIN type	6 - 300			
Cu	Dornkerbung Deep indent pressing	6 - 240			
Cu	Adenendhülsen Pressung trapezoidal pressing	10 - 185			
Cu + Al	Oval-Pressung oval pressing	10 - 95			
Cu + Al	Vorrunden Prerounding	25 - 300			
Cu	REMA WMS - Pressung REMA WMS - pressing	10 - 95			
Presseinsätze ab Seite 141 / Dies on page 141					