

Presskopf H 130


mit Hydraulik-Zylinder zum Anschluss an Hydraulik-Pumpen

- Inkl. Kupplungsnappe
- Sechskant-Pressseinsätze nach DIN 48083/Blatt 4
- Betriebsdruck: max. 700 bar
- Presskraft: 130 kN

Compression head H 130

with hydraulic-cylinder for connecting to hydraulic-pumps

- Incl. coupling male
- Hexagonal-die-sets according to DIN 48083/page 4
- Working pressure: max. 700 bar
- Force of pressure: 130 kN



Material material	Pressform compression form	Pressbereich compression range mm ²	Länge length mm	Gewicht weight kg	Kat.-Nr. cat.-no.
Cu	Sechskantpressung, handelsüblich Hexagonal pressing, standard-type	6 - 300	230	4	57995 - 00
Cu + Al	Sechskantpressung, DIN Type Hexagonal pressing, DIN type	6 - 300			
Cu	Dornkerbung Deep indent pressing	6 - 240			
Cu	Adenendhülsen Pressung trapezoidal pressing	10 - 185			
Cu + Al	Oval-Pressung oval pressing	10 - 95			
Cu + Al	Vorrunden Prerounding	25 - 240			
Cu	REMA WMS - Pressung REMA WMS - pressing	10 - 95			
Presseinsätze ab Seite 141 / Dies on page 141					

