



ELECTRICAL PRODUCTS



POWER SUPPLY SYSTEM (Surge Protective Device)

COMBINED MODULAR SPD - TYPE 1 + TYPE 2

ارسترهای خط تغذیه

ارسترهای محافظ در برابر جریان صاعقه و فراتاخت ولتاژ - کلاس 1 ترکیبی

Product Type / Code	Max. Continuous Operating Voltage U_c (V)	Lightning Impulse Current $10 / 350 \mu s$ I_{imp} (KA)	Nominal Discharge Current $8 / 20 \mu s$ I_{na} (KA)	Voltage Protection Level U_p (KV)	Temporary Overvoltage 5 sec. 0.2 sec U_T (V)	Protection Level	SPD Construction	Max. Backup Fuse (A)
PIVM7 - 75, PIVM7 - 75 DS / 16 000, 16 001	75	7	20	<0.600	---	IB-IV	Varistor	160 gL / gG
PIVM7 - 150, PIVM7 - 150 DS / 16 002, 16 003	150	7	20	<0.750	---	IB-IV	Varistor	160 gL / gG
PIVM7 - 275, PIVM7 - 275 DS / 16 004, 16 005	275	7	20	<1.2	335	IB-IV	Varistor	160 gL / gG
PIVM7 - 385, PIVM7 - 385 DS / 16 006, 16 009	385	7	20	<1.7	---	IB-IV	Varistor	160 gL / gG
PIVM7 - 440, PIVM7 - 440 DS / 16 010, 16 011	440	7	20	<2	---	IB-IV	Varistor	160 gL / gG
PIVM7 - 275 / 1+1, PIVM7 - 275 DS / 1+1 / 16 012, 16 013	275	7	20	<1.2	335, 1200	IB-IV	Varistor	160 gL / gG
PIVM7 - 275 / 2+0, PIVM7 - 275 DS / 2+0 / 16 044, 16 045	275	7	20	<1.2	335	IB-IV	Varistor	160 gL / gG
PIVM7 - 275 / 3+0, PIVM7 - 275 DS / 3+0 / 16 026, 16 027	275	7	20	<1.2	335	IB-IV	Varistor	160 gL / gG
PIVM7 - 275 / 3+1, PIVM7 - 275 DS / 3+1 / 16 018, 16 019	275	7	20	<1.2	335, 1200	IB-IV	Varistor	160 gL / gG

Approvals: CE, CCC, KCC

