



ELECTRICAL PRODUCTS



POWER SUPPLY SYSTEM (Surge Protective Device)

LIGHTNING AND SURGE ARRESTER - TYPE 1 + TYPE 2

کلاس I ترکیبی

ارسترهای خط تغذیه

ارسترهای محافظه در برابر جریان صاعقه و فراتاخت ولتاژ - کلاس I ترکیبی

Product Type / Code	Max. Continuous Operating Voltage U_c (V)	Lightning Impulse Current $10 / 350 \mu s$ I_{imp} (KA)	Nominal Discharge Current $8 / 20 \mu s$ I_n (KA)	Voltage Protection Level U_p (KV)	Temporary Overvoltage 5 sec. 0.2 sec U_T (V)	Protection Level	SPD Construction	Max. Backup Fuse (A)
SPC12.5, SPC12.5 DS	275	12.5	25	<1.2	335	I	Varistor	160 gL / gG
10 744, 10 644								
SPC12.5 / 1+1	275	12.5	25	<1.2	335, 1200	I-II-IV	Varistor	160 gL / gG
SPC12.5 DS / 1+1 / 10 740, 10 640								
SPC12.5 / 3+0	275	12.5	25	<1.2	335	I-II-IV	Varistor	160 gL / gG
SPC12.5 DS / 3+0 / 10 734, 10 634								
SPC12.5 / 3+1	275	12.5	25	<1.2	335, 1200	I-II-IV	Varistor	160 gL / gG
SPC12.5 DS / 3+1 / 10 730, 10 630								
SPC25, SPC25 DS	275	25	25	<1.2	335	I	Varistor	250 gL / gG
10 746, 10 646								
SPC25 / 1+1	275	25	25	<1.2	335, 1200	I-II	Varistor	250 gL / gG
SPC25 DS / 1+1 / 10 742, 10 642								
SPC25 / 3+0	275	25	25	<1.2	335	I-II	Varistor	250 gL / gG
SPC25 DS / 3+0 / 10 736, 10 636								
SPC25 / 3+1	275	25	25	<1.2	335, 1200	I-II	Varistor	250 gL / gG
SPC25 DS / 3+1 / 10 732, 10 632								

Approvals: CE, CCC, KEMA

