

HAND HYDRAULIC CUTTER - CUTS STEEL MATERIALS AS WELL AS CABLES UP TO 54 mm

سرقچی کابل پر هیدرولیکی دستی
۱۲ تن دو پیستونه

Code	Output force (kN)	Maximum Handle Load (N)	Length (mm)	Weight (kg)	Features	Remarks																						
S-550	124	276	625	10	● New series (heavy duty, improved design) ● Two stage pumping for rapid blade advance ● Safety relief valve for overload protection ● Guillotine type cutting for less jamming than shear type cutting ● No set-up time required ● Blades are easily replaceable ● 180 degree swivel and lock pin type head allows easy cutting position	Cutting of piano wire is prohibited. Cutting capacity <table><tr><td>Wire rope 6 × 7</td><td>: 25 mm</td></tr><tr><td>Wire rope 6 × 12</td><td>: 30 mm</td></tr><tr><td>Wire rope 6 × 19</td><td>: 30 mm</td></tr><tr><td>Soft steel bar</td><td>: 22 mm</td></tr><tr><td>Reinforcing rod</td><td>: 20 mm</td></tr><tr><td>Cu strands</td><td>: 54 mm</td></tr><tr><td>Al strands</td><td>: 54 mm</td></tr><tr><td>ACSR</td><td>: 54 mm</td></tr><tr><td>Guy wire 1 × 7</td><td>: 15 mm</td></tr><tr><td>Guy wire 1 × 19</td><td>: 20 mm</td></tr><tr><td>CCP cable</td><td>: N/A</td></tr></table>	Wire rope 6 × 7	: 25 mm	Wire rope 6 × 12	: 30 mm	Wire rope 6 × 19	: 30 mm	Soft steel bar	: 22 mm	Reinforcing rod	: 20 mm	Cu strands	: 54 mm	Al strands	: 54 mm	ACSR	: 54 mm	Guy wire 1 × 7	: 15 mm	Guy wire 1 × 19	: 20 mm	CCP cable	: N/A
Wire rope 6 × 7	: 25 mm																											
Wire rope 6 × 12	: 30 mm																											
Wire rope 6 × 19	: 30 mm																											
Soft steel bar	: 22 mm																											
Reinforcing rod	: 20 mm																											
Cu strands	: 54 mm																											
Al strands	: 54 mm																											
ACSR	: 54 mm																											
Guy wire 1 × 7	: 15 mm																											
Guy wire 1 × 19	: 20 mm																											
CCP cable	: N/A																											

