



## MECHANICAL PRODUCTS

### HYDRAULIC CUTTER HEAD - CUTS HEAVY DUTY STEEL MATERIALS UP TO 32 mm

سرقچی کابل بر هیدرولیکی دستی  
۲۰ تن

Code	Output force (kN)	Maximum Input Pressure (Mpa)	Length (mm)	Weight (kg)	Features	Remarks																						
SP-32	214	68.5	300	10	<ul style="list-style-type: none"><li>● Fast cutting with remote operation</li><li>● It can be operated by any hydraulic pump with rated oil pressure of 68.5 Mpa (10,000 PSI)</li><li>● Equipped with PT 3/8" threaded Izumi high pressure couplers</li><li>● PT-NPT adapters are available on request for NPT 3/8" threaded couplers</li><li>● Blades are easily replaceable</li><li>● Flip-top latch for easy insertion of cutting material</li></ul>	<p>Cutting of piano wire is prohibited.</p> <p>Cutting capacity</p> <table><tr><td>Wire rope 6 × 7</td><td>: 32 mm</td></tr><tr><td>Wire rope 6 × 12</td><td>: 32 mm</td></tr><tr><td>Wire rope 6 × 19</td><td>: 32 mm</td></tr><tr><td>Soft steel bar</td><td>: 25 mm</td></tr><tr><td>Reinforcing rod</td><td>: 25 mm</td></tr><tr><td>Cu strands</td><td>: 32 mm</td></tr><tr><td>Al strands</td><td>: 32 mm</td></tr><tr><td>ACSR</td><td>: 32mm</td></tr><tr><td>Guy wire 1 × 7</td><td>: 32 mm</td></tr><tr><td>Guy wire 1 × 19</td><td>: 32 mm</td></tr><tr><td>CCP cable.</td><td>: N/A</td></tr></table>	Wire rope 6 × 7	: 32 mm	Wire rope 6 × 12	: 32 mm	Wire rope 6 × 19	: 32 mm	Soft steel bar	: 25 mm	Reinforcing rod	: 25 mm	Cu strands	: 32 mm	Al strands	: 32 mm	ACSR	: 32mm	Guy wire 1 × 7	: 32 mm	Guy wire 1 × 19	: 32 mm	CCP cable.	: N/A
Wire rope 6 × 7	: 32 mm																											
Wire rope 6 × 12	: 32 mm																											
Wire rope 6 × 19	: 32 mm																											
Soft steel bar	: 25 mm																											
Reinforcing rod	: 25 mm																											
Cu strands	: 32 mm																											
Al strands	: 32 mm																											
ACSR	: 32mm																											
Guy wire 1 × 7	: 32 mm																											
Guy wire 1 × 19	: 32 mm																											
CCP cable.	: N/A																											

