

HYDRAULIC CUTTER HEAD - CUTS AL & CU CABLES UP  
TO 60 mmسرقچی کابلبر هیدرولیکی A تن  
جهت برش کابل تا قطر ۶۰ میلیمتر

Code	Output force (KN)	Maximum input Pressure (Mpa)	Length (mm)	Weight (kg)	Features	Remarks
P-60	79	68.5	410	5.8	<ul style="list-style-type: none"> <li>Fast cutting with remote operation</li> <li>Guillotine type cutting for less jamming than shear type cutting</li> <li>It can be operated by any hydraulic pump with rated oil pressure of 68.5 Mpa (10,000 PSI)</li> <li>Equipped with NPT 3/8" threaded parker type high pressure coupler</li> <li>Blades are easily replaceable</li> <li>Lock pin type cutter head</li> </ul>	Cutting of piano wire is prohibited.  Cutting capacity  Cu strands : 60 mm Al strands : 60 mm CCP cable : 60 mm  Wire rope 6 × 7 : N/A Wire rope 6 × 12 : N/A Wire rope 6 × 19 : N/A Soft steel bar : N/A Reinforcing rod : N/A ACSR : N/A Guy wire 1 × 7 : N/A Guy wire 1 × 19 : N/A

