

**HAND HYDRAULIC PUNCH - PUNCHING CAPACITY: 20.5 mm
DIAMETERS HOLE ON 13 mm THICKNESS MILD STEEL**

سرپانچر هیدروولیکی دستی
با توانایی پانچ پنج ورق تا ضخامت ۱۳ میلیمتر

Code	Specification	Size (mm)	Weight (kg)	Features	Remarks	Accessories
SH-70A	Throat depth : 70 mm Oil volume required: 82 cc Output force : 304 KN at 68.5 Mpa pressure	360×210 ×95	13	The portable SH-70A punch was designed to punch holes through 13 mm mild steel, aluminum and copper. A stripper guide extends on either side of the ram to strip the material after punching. This powerful punch will operate from any 68.5 Mpa (10,000 PSI) hydraulic pump. The SH-70A comes complete with four sets of punch an die sizes for 3/8" , 1/2" , 5/8" and 3/4" bolts, hand pin, carrying case.	- Powerful perforation up to 13 mm thick mild steel with a 20.5 mm maximum hole - Recommended for angle iron, plates, beams and bus bars - Stripper guide extends to grip material before punching so that bending and binding or slippage can be avoided - Stripper guide clamps punch in place to free operator's hands 70 mm throat depth allows commonly used angle iron	Punch & Die for mild steel: 10.5, 13.5, 17.5, 20.5 mm diameter, Hand pin, steel carrying case

