

MECHANICAL PRODUCTS

HYDRAULIC PUMP (ENGINE DRIVEN) - RATED PRESSURE: 68.5 MPA

پمپ هیدرولیکی بنزینی تک شلنگه ۷۰۰ بار با ریموت کنترل سیمی

68.5 MPA						ا ريسوت عسرن سيسي
Code	Specification	Size (mm)	Weight (kg)	Features	Remarks	Accessories
HPE-1A	Oil delivery:	470×320	30	The HPE-1A single acting gasoline	Hydraulic hose sold separately.	Remote control switch,
	2.6 liter /	×390		engine driven hydraulic pump is the		Spark plug wrench
	min at low pressure			most sophisticated engine pump on	Remote control operation	100
	0.5 liter /			today's market. It builds pressure to		
	min at high pressure			68.5 Mpa automatically and returns	Pole mounting bracket as a	
	Engine: Air seeled			engine RPM to an idle.	standard accessory	
	Engine: Air cooled			Wired remote control allows operator	- No 1 - 7 I 1	
	4 cycle gasoline engine 1.0 kw (1.4 ps) /			complete control Oil volume is large	Visual oil level	
	3,600 rpm , leadfree			enough to operate a 60 ton class	External air vent and oil level	
	gasoline			single acting compression head.	External all vent and on level	
					Compact design	
	Reservoir capacity:					
	2.2 liter				Dependable Fuji Heavy's engine	
					For single acting tools	

