

**HYDRAULIC PUMP(ENGINE DRIVEN) - RATED PRESSURE:
68.5 MPA**

پمپ هیدرولیکی بنزینی تک شلنگه ۷۰۰ بار
با ریموت کنترل

Code	Specification	Size (mm)	Weight (kg)	Features	Remarks	Accessories
HPE-3SA	<p>Oil delivery: 3.3 liter / min at low pressure 1.1 liter / min at high pressure</p> <p>Engine: Air cooled 4 cycle gasoline engine 2.0 kw (2.7 ps) / 3,600 rpm , leadfree gasoline</p> <p>Reservoir capacity: 5 liter</p>	650×370 ×500	49	<p>The HPE-3SA single acting engine driven hydraulic pump suitable for single acting presses for transmission line use.</p> <p>This pump is one of the most sophisticated on today's market. It builds pressure to 68.5 Mpa automatically, and returns the engine RPM to an idle. The push button will control the fluid flow at the discretion of the operator. There is also a manual mode on the pump that can be used to override the remote control.</p> <p>Electric circuit boards are completely modulated for easy replacement and repair.</p>	<p>Hydraulic hose sold separately.</p> <ul style="list-style-type: none"> Wired Remote control operation with manual control lever Auto operation allows fully automatic compression work, advance - 68.5 Mpa - retraction of ram , by just pressing UP button once on the remote control switch Compression counter to monitor compression cycles for the remainder of maintenance schedule Pressure gauge for easy output confirmation Reliable output by FUJI HEAVY'S engine For single acting tools 	Remote control switch, Spark plug wrench

