

MECHANICAL PRODUCTS

HYDRAULIC PUMP(ENGINE DRIVEN) - RATED PRESSURE: 68.5 MPA

پمپ هیدرولیکی بنزینی دو شلنگه ۷۰۰ بار با ریموت کترل سیمی

68.5 MPA					ب ريموت عمرن سيسي	
Code	Specification	Size (mm)	Weight (kg)	Features	Remarks	Accessories
HPE-1D	2.6 liter /	530×330 ×415	33	The HPE-1A double acting gasoline engine driven hydraulic pump is the most sophisticated engine pump on	Hydraulic hose sold separately.	Remote control switch, Spark plug wrench
	min at low pressure 0.6 liter /			today's market. It builds pressure to	Remote control operation	
	min at high pressure			68.5 Mpa automatically and returns engine RPM to an idle.	Visual oil level	
	Engine: Air cooled 4 cycle gasoline engine			Wired remote control allows operator	 External air vent and oil level 	
	1.0 kw (1.4 ps) / 3,600 rpm , leadfree			complete control. Oil volume is large enough to operate a 100 ton class	Compact design	
	gasoline Reservoir capacity: 2.2 liter			double acting compression head for intermittent use.	 Solenoid operated 4 way valve (For double acting tools) 	
	2.2 IIIGI				Dependable Fuji Heavy's engine	

